

## ENTHRONE 29 (29-inch Sheetfed Offset Press) Specifications

Model		E-229	E-429	E-529	
Number of colors		2	4	5	
Max. printing speed	sph	13,000			
Max. sheet size	mm (in.)	530x750 (20 <sup>7/8</sup> x 29 <sup>17/32</sup> )			
Min. sheet size	mm (in.)	200x280 (7 <sup>7/8</sup> x 11 <sup>1/32</sup> )			
Max. printing area	mm (in.)	520x740 (20 <sup>15/32</sup> x 29 <sup>1/8</sup> ) [520x736 (20 <sup>15/32</sup> x 28 <sup>31/32</sup> ) option]			
Sheet thickness range	mm (in.)	0.04~0.6 (0.0016~0.024)			
Plate size	mm (in.)	605x760 (23 <sup>13/16</sup> x 29 <sup>29/32</sup> ) [605x745 (23 <sup>13/16</sup> x 29 <sup>11/32</sup> ) option]			
Blanket size	mm (in.)	678x770 (26 <sup>11/16</sup> x 30 <sup>5/16</sup> ) [Including aluminum bar]			
Feeder pile height	mm (in.)	800 (31 <sup>1/2</sup> )			
Delivery pile height	mm (in.)	600 (23 <sup>5/8</sup> )			
Dim.	Length (L)	mm (ft.)	4,594 (15')	6,322 (20'9")	7,186 (23'7")
	Width (W)	mm (ft.)	2,520 (8'3")		
	Height (H)	mm (ft.)	1,770 (5'10")[*2,147 (*7')]		
Weight	kg (lb.)	8,100 (17,857)	14,300 (31,526)	17,400 (38,360)	
Power consumption (50Hz)	kW	28.5	36.5	47.0	
	(60Hz) kW	30.0	38.0	48.5	

Note:

1. The max. printing speed is subject to change depending on the paper quality, paper thickness, printing contents and other conditions.

2. Power consumption may differ on machines with user-mounted options or devices.

3. \* is the height up to the guardrail of the operation stand.